



MAXIVOLT.COM
 SERIOUS SURGE PROTECTION®
 MADE IN THE USA • SINCE 1988

GUARDDOG® WRG-200N


- Primary and Secondary Protection Circuits
- Primary and Secondary Safety Fusing
- Primary and Secondary Dry Contacts
- Audible Alarm Option
- NEMA® 4X Rated Enclosure
- Listed to ANSI/UL 1449-4 & IEC 61643-11
- One Year Warranty
- Made in the USA



WRG-200N Surge Protective Device

Maxivolt GuardDog® • Made in USA • Serious Surge Protection • Made in USA • Maxivolt GuardDog® • Made in USA • Serious Surge Protection • Made in USA • Maxivolt GuardDog®

Approx. 9.5"H 7.5"W 5.7"D



Application

Voltage 120 / 240 VAC
 Configuration 3 Ø / 4 Wire

Characteristics

Fusing Internal
 Indication Blue LEDs On / Red LEDs Off
 Conductor 12 AWG Stranded
 Enclosure NEMA® Type 4X

Certifications

Listing ANSI/UL 1449 Ed. 4 / IEC 61643-11
 Environmental RoHS

Specifications


Modes of Protection L-N, L-L
 Type (Class) II (2)
 Clamp Voltage L-N (L-L) [Hi-Leg] 220 (440) [510]
 VPL L-N (L-L) [Hi-Leg] 500 (960) [900]
 VPR L-N (L-L) [Hi-Leg] 700 (1000) [1200]
 SCCR 100 kA
 MCOV L-N (L-L) [Hi-Leg] 140 (280) [300]
 Operating Temperature -40° C to 85° C
 Operating Humidity 1% to 95%
 Filtering UL 1283
 EMI-RFI Noise Attenuation < 40 db
 Capacitance 1 to 1.5 µF / Line
 Component Response Time < 1 ns
 Frequency Range 50 - 400 HZ
 Dry Contact Interface 24 VDC - 240 VAC
 Relay Max Current 2 Amps

Standard Installation Diagram

Install According To Instructions Provided With Device

Note: For optimum performance, minimize conductor length and avoid sharp bends.

Note: Connect Normally Open or Normally Closed conductor to input of the system control interface. The alarm interface may alternatively be connected to an audible alarm or visual indicator.



Maxivolt Corporation
 800 South Rusk Street
 Amarillo, Texas, USA

(806) 371-0722
 (800) 583-4773
 www.maxivolt.com